

ECONO-GRADE SIZING INSPECTION COMBO

SIZE, ELIMINATE DEBRIS, AND INSPECT ALL ON ONE SINGLE SYSTEM

LAKWOOD Econo-Grade
PROCESS MACHINERY

- All stainless steel construction
- Precision machined spools ensure exact diameter sizing
- Sizing section mounts directly onto Inspection Conveyor
- Includes lug rack to catch disregarded berries and debris
- Easy wipe-clean design
- 3" hinged flip-up trash lanes on each side
- Removable spools for easy changeover to different sizing spools

A metering hopper conveyor feeds berries onto the profile roller bed which has openings for small berries and debris to drop out. Large berries flow across the roller bed onto the manual inspection conveyor, and large defect berries are manually removed from the inspection conveyor. As defect berries and debris are removed, they are placed into the trash lanes on either side of the conveyor, and conveyed into lugs held underneath the inspection conveyor.

Econo-Grade Capacities

Working Width	Length	Capacity (lbs per hour)
24"	10'	Apprx 2,500 lbs per hour
24"	14'	Apprx 2,500 lbs per hour
30"	14'	Apprx 3,500 lbs per hour

Econo-Grade Conveyor Style Options

Conveyor Options
Rubber Belt

Econo-Grade Size Gap Options

Sizing Spool Options
9mm Size Gap
10.5mm Size Gap
12mm Size Gap
1/2" Size Gap

